INNOVATIVE PRODUCTS AND SERVICE FOR CONSTRUCTION **PROJECTS AND AUTOMATIVE** SERVICE

> Email:sales@wiremeshprovider.com admin@wiremeshprovider.com WhatsApp and phone: +8619903282767 Location:High-tech Development Zone, Anping County, Hengshui City, Hebei Province

land lesh Wire Mesh



On the Forefront of Architectural Innovation





About Yang Zhe Metal

Hebei Yangzhe Metal Wire Mesh Co., Ltd. is a professional manufacturer of decorative metal sheets located in Anping, Hebei, China. The factory was established in 2008 and has the widest range of products, including perforated metal sheets, expanded metal sheets, etc. As a manufacturing and trading combination, we have stamping, laser cutting, metal workshop welding and quality inspection departments are expanding. Due to the high quality of our products, we have excellent customer service and our sales network covers the United States, the Middle East, Europe and Africa. Just send us your design drawings and pictures, and we can tailor a solution for you. Our sales department has experienced foreign trade sales staff who can provide you with professional design and development services to turn your ideas into reality.



About Yang Zhe Metal

Introduction

al Materials

l Speci**fi**cation

Shapes

ingement



Page Of Content

Brief Introduction

Perforated metal sheets



Perforated metal sheets are famous for its high strength-to-weight ratio. Today, these decorative punching panels have become the preferred choice for intricate and effective architectural designs. They are cost-efficient and aesthetic for acoustic applications, exterior or interior features. Artists love to apply these dynamic metal sheets to churches, offices, airports, restaurants, gymnasiums, music rooms, concert halls, bars, shopping malls, etc.

General Materials









Copper Model: 110, 220, 230, 260, 268, 270, 335, 340, 342, 353, 443, 444, 445, 464, 465, 466, 467, 614, 705, 715, etc.



Aluminum

Aluminum perforated metal sheets are lightweight and corrosion resistant. Multifarious brilliant colors are available after anodizing or coating.

Aluminum Model: 1060 aluminum, 3003/5005 aluminum alloy.

Galvanized steel

We adopt hot dipped galvanized steel as the general material. It can keep your facade panel from corrosion damaged for decades.

Steel Model:

AISI 1018/1144/12L14/8620, ASTM A36/A653/ A366/A513.

Stainless steel

Austenitic stainless steel has the best process properties since its good plasticity. Martensitic stainless steel has a lower technological performance because of its higher hardness.

Stainless Steel Model: 304, 316, 430, 410, 301, 302, 303, 321, 347, 416, 420. 430. 440. etc.

Copper

Featured with its inherent nobleness touch, it offers the perforated panels more charming.

General **Specification**

Thickness

Standard: 0.5–12 mm **Customize:** can be up to 20 mm.

- Width: 0.8-2.0 m.

- Length: up to 11.8 m or in coils.
- Standard Size: 1 m × 2 m, 1.22 m×2.44 m, 1.5 m× 3 m, etc.
- Hoe Diameter: 5-100 mm.

- Hole Arrangement: straight, staggered.
- **Opening Area:** 7% 83%.
- Personalized Pattern Design: available.
- Main Types: safe margins or no-margins.
- End Types: finished or unfinished.
- Fabrication Methods: welded or lock seam.

Surface Treatment



Suitable material: carbon steel.

Hot Dipped Galvanized

Hot-dip galvanizing is the most widely used and cost-effective steel surface treatment method. It plays an invaluable and irreplaceable role in the corrosion resistance and energy saving of steel. The hot-dip galvanized perforated metal panel will not rust in a few years.



Suitable material: stainless steel

2B/2D/2R Mill Finish

Mill finish refers to the surface texture (or finish) of metal after it is processed by a rolling mill, extrusion die or drawing. Or rather, it is the basic supply condition for all stainless steel panels products. The 2B surface is a bright cold-rolled surface that is very similar to the 2D surface.



Suitable material: aluminum or aluminum alloys.

Anodizing

This is an electrolytic oxidation process in which the surfaces of aluminum or aluminum alloys are usually converted into an oxide film. Thereby improving the corrosion resistance, wear resistance and hardness of the metal plate. There are a variety of beautiful colors available.



Suitable material: aluminum or aluminum alloys.

Fluorine Carbon Spraying

Fluorocarbon coating is a high-grade spray coating. It has excellent performance of anti-fading, anti-blooming and antiair pollution (acid rain, etc.), as well as strong crack & UV resistance and ability to withstand harsh weather conditions.





Suitable material: carbon steel, aluminum or aluminum alloys.

Powder Coated

Powder coating, a dry finishing process, is applied as a free-flowing, dry powder. The main categories of powder coating include thermosets and thermoplastics. As a result, it can create a hard finish that is tougher than conventional paint.



Rust paint

Rust paint is a retro and fashionable surface treatment method. Finished effect has a fine texture to form a natural texture of real metal corrosion. The rust painted perforated metal sheet has been used in bars, clubs, cafes, stadiums in recent years.

Hole Shapes

Round Hole

The most classic and proposed hole shape. It can blend into the surrounding environment naturally.





Slotted Hole

Slender and decorative hole shape. It provides greater air ventilation and passage than the round hole perforation.

2

Square Hole

Well-regulated mesh arrangement. It has light weight and provides a larger opening area.





Open area can be up to 80%. If you want to have a superb vision, it will be the best choice.

Triangular Hole

Triangles are synonymous with stability. It provides natural light & ventilation while maintaining privacy.





Decorative Hole

Showing picture is just a representation. There are virtually thousands of patterns provide for you.









Decorative Perforated Metal Sheets



Round Hole (Straight Pattern)

Perforation diameter (d) Center distance (c)





Open area (%) 50.2 40.1 34.9 19.6 42.2 31.0 19.6 41.9 54.5 40.1 19.6 50.1 34.9 44.2 28.3 19.6 55.7 13.9 47.5 35.6 44.2 35.0 50.2 41.5 54.5 40.1 50.2 34.9 54.5



Round Hole (45 °C Staggered)

Perforation diameter (d) Center distance (c)

d (mm)	c (mm)	Open area (%)	d (mm)	c (mm)	Open area (%)	d (mm)	c (mm)
0.4	1.5	5.6	8	10	50.2	20	25
0.5	1.5	8.7	8	12	34.9	20	28
0.8	1.8	15.5	8	16	19.6	20	30
1	1.5	34.9	9	12	44.2	20	40
1	2	19.6	9	18	19.6	22	30
1.5	2.5	28.3	10	12	54.5	22	35
1.5	3	19.6	10	14	40.1	22	44
2	3	34.9	10	20	19.6	23	31.5
2	3.5	25.6	11	13	56.2	25	30
2	4	19.6	11	15	42.2	25	35
2.5	4	30.7	12	14	57.7	25	50
2.5	4.5	24.2	12	16	44.2	25.4	31.8
2.5	5	19.6	12	18	34.9	25.4	38.1
3	5	28.3	12	24	19.6	30	40
3	6	19.6	14	16	60.1	30	50
3	8	11.0	14	18	47.5	30	60
4	6	34.9	14	20	38.5	32	38
4	8	19.6	15	20	44.2	32	76
5	7	40.1	15	30	19.6	35	45
5	8	30.7	16	20	50.2	35	52
5	9	24.2	16	22	41.5	38.1	50.8
5	10	19.6	16	32	19.6	38.1	57.1
6	8	44.2	17	22	46.9	40	50
6	9	34.9	17	25	36.3	40	55
6	10	28.3	18	22	52.5	50	60
6	12	19.6	18	25	40.7	50	70
7	9	47.5	18	26	37.6	50.8	63.5
7	10	38.5	19	25.4	43.9	50.8	76.2
7	14	19.6	19	28.5	34.9	63.5	76.2

d (mm)	c (mm)	Open area (%)	d (mm)	c (mm)	Open area (%)	d (mm)	c (mm)	Open area (%)
0.8	2.5	16.1	5	25	6.3	13	40	16.6
2	6	17.4	5	28	5.0	14	30	34.2
2	7.5	11.2	5	30	4.4	14	32	30.1
2	8	9.8	6	10	56.5	14	34	26.6
2.5	8	15.3	6	16	22.1	15	34	30.6
3	8	22.1	6	20	14.1	15	40	22.1
3	12	9.8	6	30	6.3	16	34	34.8
3	14	7.2	6.3	30	6.9	16	40	25.1
3	27	1.9	7	14	39.3	16	45	19.8
3.2	8	25.1	8	18	31.0	16	90	5.0
3.6	8	31.8	8	30	11.2	18	34	44.0
4	8	39.3	10	27	21.5	18	56	16.2
4	12	17.4	10	28	20.0	20	40	39.3
4	45	1.2	10	30	17.4	20	50	25.1
5	9	48.5	10	45	7.8	26	50	42.5
5	12	27.3	12	27	31.0	32	60	44.7
5	14	20.0	12	28	28.8	40	72	48.5
5	20	9.8	12	50	9.0	50	92	46.4



Open area (%) = $1.57 \times \frac{d^2}{c^2} \times 100$



Hole Arrangement

Round Hole (60 °C Staggered)

Perforation diameter (d) Center distance (c)

Open area (%) =
$$0.91 \times \frac{d^2}{a^2} \times 100$$



Square Hole (Straight Pattern)

Perforation diameter (d) Center distance (c)

d	С	Open area	d	С	Open area	d	С	Open area	d	С	Open area
(mm)	(mm)	(%)	(mm)	(mm)	(%)	(mm)	(mm)	(%)	(mm)	(mm)	(%)
0.4	1.5	6.5	3.6	5.5	39.0	7	11.25	35.2	15	21	46.4
0.5	1.5	10.1	3.6	6	32.8	7	14	22.8	15	24	35.5
0.6	1.2	22.8	3.6	7	24.1	7	20	11.1	16	18	71.9
0.8	1.5	25.9	4	5	58.2	8	10	58.2	16	20	58.2
1	2	22.8	4	6	40.4	8	10.6	51.8	16	24	40.4
1.2	2.5	21.0	4	7	29.7	8	11	48.1	16	30	25.9
1.5	2.5	32.8	4	8	22.8	8	11.25	46.0	16	35	19.0
1.5	3	22.8	4	8	22.8	8	12	40.4	17	20	65.7
1.6	2.5	37.3	4	12.5	9.3	8	13.5	32.0	17	22	54.3
1.6	3	25.9	4.5	6	51.2	8	15	25.9	18	22	60.9
1.6	3	25.9	4.5	6.5	43.6	8	16	22.8	18	24	51.2
1.8	2.5	47.2	4.5	7	37.6	8	20	14.6	19	22	67.9
1.8	3	32.8	4.5	8	28.8	8	31.2	6.0	19	25.4	50.9
2	3	40.4	4.5	15	8.2	9	12	51.2	19.5	28	44.1
2	3.5	29.7	5	6	63.2	9	18	22.8	20	28	46.4
2	4	22.8	5	7	46.4	10	12	63.2	20	30	40.4
2	5	14.6	5	7	46.4	10	13	53.8	20	35	29.7
2	5.5	12.0	5	8	35.5	10	13.5	49.9	21	30	44.6
2	14	1.9	5	9	28.1	10	14	46.4	22	30	48.9
2.25	3.5	37.6	5	10	22.8	10	15	40.4	22	32	43.0
2.25	4	28.8	5	12	15.8	10	17.5	29.7	22	80	6.9
2.5	3.5	46.4	5	19.5	6.0	10	18	28.1	22	96	4.8
2.5	3.6	43.9	5.5	8	43.0	10	20	22.8	23	35	39.3
2.5	4	35.5	5.5	9	34.0	10	22	18.8	24	35	42.8
2.5	5	22.8	5.5	10	27.5	10	25	14.6	25	30	63.2
2.5	6	15.8	6	7	66.9	11	16	43.0	25	35	46.4
2.5	9	7.0	6	8	51.2	11	17	38.1	25	50	22.8
3	4	51.2	6	10	32.8	12	14	66.9	25.4	38.1	40.4
3	4.5	40.4	6	12	22.8	12	15	58.2	29	45	37.8
3	5	32.8	6	12	22.8	12	16	51.2	30	38	56.7
3	6	22.8	6	16	12.8	12	18	40.4	30	40	51.2
3	7	16.7	6	17.5	10.7	12	19.5	34.5	30	45	40.4
3	10	8.2	6.2	7.5	62.2	12	20	32.8	32	45	46.0
3	12	5.7	6.3	9	44.6	12	22	27.1	35	47	50.5
3.2	4.5	46.0	6.3	12	25.1	12	26	19.4	35	50	44.6
3.2	4.76	41.1	6.4	12	25.9	13	18	47.5	40	56	46.4
3.2	5	37.3	6.5	9	47.5	13	30	17.1	45	64	45.0
3.2	7	19.0	6.5	24	6.7	14	20	44.6	50	65	53.8
3.5	5	44.6	7	9	55.0	14	22	36.9	50	80	35.5
3.6	5	47.2	7	10	44.6	14	26	26.4	50.8	63.5	58.2
			7	11	36.9	14	30	19.8	60	128	20.0
						15	20	51.2	65	90	47.5

		Oben area	d	C	Open area	d	С	Open area
(mm)	(mm)	(%)	(mm)	(mm)	(%)	(mm)	(mm)	(%)
2	4	25.0	10	24	17.4	22.4	28	64.0
3	5	36.0	10	26	14.8	25	28.5	76.9
3	6	25.0	10	27	13.7	25	34	54.1
4	7	32.7	10	34	8.7	25	35	51.0
4	8	25.0	10	38	6.9	25	36	48.2
5	7	51.0	10	50	4.0	25	45	30.9
5	7.5	44.4	11	15	53.8	25	50	25.0
5	8	39.1	12	17	49.8	25	56	19.9
5	10	25.0	12	18	44.4	25	64	15.3
5	14	12.8	12	30	16.0	25	68	13.5
5	15	11.1	13	18	52.2	25	70	12.8
5	16	9.8	15	20	56.3	25	72	12.1
5	20	6.3	15	21	51.0	30	35	73.5
5.5	8	47.3	15	23	42.5	30	36	69.4
6	7	73.5	15	24	39.1	30	40	56.3
6	9	44.4	15	32	22.0	30	76	15.6
6	10	36.0	15	45	11.1	33	60	30.3
8	10	64.0	16	20	64.0	35	40	76.6
8	12	44.4	16	25	41.0	35	60	34.0
8	14	32.7	18	24	56.3	35	90	15.1
8	15	28.4	18	38	22.4	36	102	12.5
8	20	16.0	19	26	53.4	39	49	63.3
8	24	11.1	20	26	59.2	40	44	82.6
8	28	8.2	20	28	51.0	40	50	64.0
8	29	7.6	20	30	44.4	40	55	52.9
9	13.5	44.4	20	32	39.1	40	72	30.9
10	12	69.4	20	40	25.0	40	100	16.0
10	13	59.2	20	50	16.0	43	50	74.0
10	13.5	54.9	20	52	14.8	44.5	52	73.2
10	14	51.0	20	56	12.8	45	78	33.3
10	15	44.4	22	28	61.7	50	65	59.2
10	16	39.1	22	30	53.8	50	92	29.5
10	20	25.0	22	56	15.4			



Open area (%) = $\frac{d^2}{c^2} \times 100$



Square Hole (Staggered Pattern)

Perforation diameter (d) Center distance (c)

10

11

12

mm

14

14

15

15

16

19

20

20

21

22.4

23

25

25

30

15

Open area (%) =
$$\frac{d^2}{c^2} \times 100$$

16

24

18

21

Open area

(%)

33

39

21

44

51

Open area

(%)

40.8

38.3

51.0

50.0

56.9

50.0 40.5

45.1

50.0

26.4

55.1

47.4

50.0

64.6

50.0

61.7



36

40

40

45

C	- D	
c (mm)	Open area (%)	
24	56	
28	505	

48

56

62

60



Short edge (a) Edge length (b) Vertical center distance (c) Horizontal center distance (C1)

Short edge (a) Edge length (b)

a × b (mm)	c × c ₁ (mm)	Open area (%)	a × b (mm)	c × c ₁ (mm)	Open area (%)	a × b (mm)	c × c ₁ (mm)	Open area (%)
1 x 15	6 x 24	20.5	5 x 15	9 x 40	38.7	10 x 30	32 x 35	49.7
1 x 15	6 x 20	24.6	5 x 35	18 x 40	47.1	10 x 35	32 x 40	51.3
2.2 x 25	10 x 30	36.0	6 x 15	22 x 20	37.4	10 x 40	16 x 92	51.4
2.5 x 25	10 x 30	40.8	6 x 25	22 x 30	43.1	10 x 60	50 x 68	34.0
3 x 30	15 x 40	29.4	6 x 40	20 x 40	58.1	10 x 65	18 x 150	46.6
3 x 35	15 x 40	34.4	6.3 x 25	17 x 35	50.1	12 x 20	44 x 30	31.7
3 x 60	18 x 68	29.1	7 x 35	26 x 40	45.1	12 x 35	35 x 80	27.8
4 x 25	16 x 30	40.2	8 x 20	26 x 32	35.2	14 x 35	36 x 80	31.1
4 x 28	35 x 35	17.7	8 x 35	14 x 82	46.4	14 x 65	24 x 150	48.2
4 x 57	18 x 68	36.7	9 x 35	32 x 40	46.5	16 x 35	42 x 80	30.1
5 x 15	20 x 20	34.8	10 x 20	40 x 30	29.8	16 x 40	24 x 96	50.8
						18 x 65	28 x 150	52.4



8

10

12.5

12

8

Open area

(%)

25

25

25

25

44.5

Square Hole (45 °C Staggered)

mm

18

20

25

30

31.5

35

Perforation diameter (d) Center distance (c)

Open area (%) =
$$2 \times \frac{d^2}{c^2} \times 100$$

31

32

29.7

30

30 32

40

40

40

55

40

46

46

44

50

54

С	Open area
(mm)	(%)
7.5	32.0
10	32.0
12	34.7
14	36.7
16	28.1
16	31.0
18	30.2
20	32.0
24	22.2
22.5	39.5
24	34.7
24	50.0
25.5	44.3
27	39.5
28	50.0
	c (mm) 7.5 10 12 14 16 16 16 18 20 24 22.5 24 22.5 24 22.5 24 22.5 24 22,5 24 22,5 24 22,5 24 22,5 24 22,5 24 22,5 24 22,5 24 22,5 24 22,5 24 22,5 24 22,5 24 22,5 27 28

14 28.3 48.9

	C	420
d	С	Open ar
(mm)	(mm)	(%)
30	60	50.0
30	65	42.6
31.5	60	55.1
32	60	56.9
34	60	64.2
ZE	60	691

30	65	42.6
31.5	60	55.1
32	60	56.9
34	60	64.2
35	60	68.1
35	63.6	60.6
40	72	61.7
45	74	74.0
45	78	66.6
50	92	59.1
55	102	58.2
60	114	55.4
100	170	69.2
120	230	54.4

a×b (mm)	C × C ₁ (mm)	Open area (%)	a×b (mm)	C × C ₁ (mm
8 x 40	44 x 22	31.6	10 x 25	26 x 2
8 x 45	44 x 22	35.8	10 x 30	25 x 2
8 x 56	54 x 54	14.9	10 x 30	30 x 3







c × c ₁ (mm)	Open area (%)	a × b (mm)	c × c ₁ (mm)	Open area (%)
26 x 26	33.8	10 x 56	54 x 27	36.9
25 x 25	44.6	12 x 39	38 x 38	30.3
30 x 30	30.9	16 x 60	80 x 50	22.6
		20 x 45	42 x 42	46.1







Round

a × b (mm)	c × c ₁ (mm)	Open area (%)
2 x 20	8 x 26	18.8
3 x 25	8 x 29	31.5
4 x 12	8 x 16	34.8
4 x 25	16 x 50	12.1
4 x 28	10 x 34	31.9
4 x 57	18 x 68	18.3
5 x 25	10 x 29	41.3
5 x 25	16 x 34	22.0
5 x 26	7 x 30	53.6
5 x 30	10 x 34	42.5
5 x 34	16 x 39	24.8

5

1 1

> d (mm)

> > 14

16

16

18

20

20

a × b (mm)	c × c ₁ (mm)	Open area (%)	a × b (mm)	c × c ₁ (mm)	Open area (%)
x 45.5	20 x 70	14.3	12 x 65	20 x 146	25.7
5 x 35	24 x 42	20.1	16 x 28	24 x 76	21.5
5 x 38	11 x 52	38.5	16 x 32	24 x 80	23.8
5 x 50	24 x 58	21.0	16 x 36	48 x 44	24.7
7 x 25	18 x 35	26.1	16 x 60	28 x 150	21.5
3 x 40	14 x 92	23.8	20 x 40	28 x 50	51.0
0 x 20	40 x 30	14.9	20 x 40	28 x 48	53.1
0 x 40	16 x 92	25.7	24 x 50	36 x 58	51.5
0 x 60	50 x 68	17.0	24 x 74	38 x 84	51.8
2 x 35	22 x 45	39.3	30 x 60	70 x 250	9.2
2 x 40	18 x 92	27.1	40 x 60	100 x 72	28.6





\bigcirc
\sim
)
)

Hexagonal Hole (60 °C Staggered)

Perforation diameter (d) Center distance (c)

Open area (%) =
$$\frac{d^2}{c^2} \times 100$$

(mm)

21

21

34

25

26

28

Open area

(%)

44.4

58.1

22.1

51.8

59.2

51.0

40 x 100 80 x 375

12.2

d (mm)	c (mm)	Open area (%)
8	10.5	58.1
8	12	44.4
10	15	44.4
10	18	30.9
10	28	12.8
12	16	56.3

a × b (mm)	c × c ₁ (mm)	Open area (%)
22	30	53.8
25	35	51.0
30	44	46.5
32	40	64.0
35	48	53.2
36	48	56.3
50	65	59.2

•••••
•••••



Hexagonal



Pentagram

Inscribed





Square





Triangular







Star

Patterns



Staggered

Curtain

Circular

4 bar

Wave



Patterns





Cymophane







Open Area

Take round hole (60 °C staggered) for example.

Hole Finishing

Take round hole and square hole for example.

Perforation diameter (d): 2.8 mm Center distance (c): 7 mm Open area: 1.4%



Perforation diameter (d): 4 mm Center distance (c): 6 mm Open area: 40.4%



Perforation diameter (d): 10 mm Center distance (c): 25 mm Open area: 14.6%



Perforation diameter (d): 22 mm Center distance (c): 32 mm Open area: 43.0%



Perforation diameter (d): 3.2 mm Center distance (c) 7 mm Open area: 19.0%

Center distance (c): 7 mm

Open area: 46.4%



Perforation diameter (d): 3.6 mm Center distance (c): 7 mm Open area: 24.1%



Center distance (c): 10 mm Open area: 27.5%



Perforation diameter (d): 5 mm Center distance (c): 6 mm Open area: 63.2%



Perforation diameter (d): 19.5 mm Center distance (c): 28 mm Open area: 44.1%



Perforation diameter (d): 45 mm Center distance (c): 64 mm Open area: 45.0%



Unfinished - Round



Unfinished – Square

Edge Finishing

Take round hole for example.





safe margins

lack of margins





Perforation diameter (d): 29 mm Center distance (c): 45 mm Open area: 37.8%





Perforation diameter (d): 16 mm Center distance (c): 30mm Open area: 25.9%



Perforation diameter (d): 35 mm Center distance (c): 50 mm Open area: 44.6%





Finished - Round

Finished – Square



no-margins

Decorative Perforated Metal Sheets



We can CNC punch the architectural decorative panels from stainless steel, galvanized steel and aluminum as well as copper and brass. Simple shapes include square, round or hexagonal can be formed directly on the sheet. And complex patterns can combine different holes shapes and sizes on one metal plate at high producing speed.

Advantage

- High efficiency production..
- Various patterns, accurate hole size.
- Increased throat deep and working area.
- Can be painted, galvanized or polished.

Parameters

Basic Parameters of CNC Punching Perforated Metal Panels

Panel Size (m)	Panel Thickness (mm)	Punching Speed	Perforation Diameter (mm)
W × L	Max.		Max.
1.5 × 3	8	Up to 3000 strokes/	89
1.27 × 2.5	8	(high marking mode)	89
1.5 × 2.25	8		89

*Bespoke orders are acceptable for various imaginable designs.

We adopt a high power density laser beam to irradiate the materials. As the laser beam moves over the sheet, the hole continuously forms a slit having a narrow width (e.g., about 0.1 mm) to complete the cutting of the material.

Advantage

- Material saving, low production cost...
- Ideal for all kinds of metal based materials.
- Detailed and precise cutting patterns.
- Zero damage to materials during cutting.

Basic Parameters of Laser Cutting Perforated Metal Panels

Panel Size (m)	Panel Thickness (mm)		
W × L	Aluminum	Steel	Stainless Steel
2.5 × 4	0.5-12	0.5-25	0.5–20
1.5 × 3	0.5-5	0.5-15	0.5-6
1.5 × 4	0.5-8	0.5-20	0.5-12

*Bespoke orders are acceptable for various imaginable designs.



Parameters

Application Field

Our products have extremely broadly applications. Artists love to apply these dynamic metal sheets to churches, offices, airports, restaurants, gymnasiums, music rooms, concert halls, bars, shopping malls, etc.

















